

**Required information for RVU in  
COMMISSION REGULATION (EU) No. 1254/2014 ANNEX IV**

(a)	Supplier's name	mitsubishi electric
(b)	Model name	LGH-25RVX-E
(c)	SEC (kWh/(m2.a))	Cold region: -78.4 Average region: -41.1
(d)	Declared typology	RVU,BVU
(e)	Type of drive	Multi-speed
(f)	Type of HRS	Recuperative
(g)	Thermal efficiency (%)	80
(h)	Maximum flow rate (m3/h)	215
(i)	Electric power input (kW)	0.062
(j)	Casing sound power level (dB)	42
(k)	Reference flow rate (m3/s)	0.05
(l)	Reference pressure difference (Pa)	48
(m)	SPI (W/(m3/h))	0.18
(n)	Control factor and typology	Local demand control
(o)	Maximum leakage rate (%)	10% or less
(p)	Mixing rate of non-ducted	-
(q)	Visual filter warning	Refer to instruction book
(r)	Instructions to install regulated supply/exhaust grilles for unidirectional ventilation	-
(s)	Internet address for disassembly instructions	<a href="http://erp.mitsubishielectric.eu/">http://erp.mitsubishielectric.eu/</a>
(t)	Airflow sensitivity for non-ducted units	-
(u)	air tightness for non-ducted units	-
(v)	AEC (kWh/a)	Average region: 1.7
(w)	AHS (kWh primary energy/a)	Average: 44.7 Cold: 87.4 Warm: 20.2

**MITSUBISHI ELECTRIC CORPORATION**

Manufactured by: MITSUBISHI ELECTRIC CORPORATION

TOKYO BLDG., 2-7-3, MARUNOUCHI, CHIYODA-KU, TOKYO 100-8310, JAPAN

Importer in EU: MITSUBISHI ELECTRIC EUROPE B.V.

HARMAN HOUSE, 1 GEORGE STREET, UXBRIDGE, MIDDLESEX, UB8 1QQ, U.K.



**ENERG**

енергия · ενεργεια



Model **LGH-25RVX-E**



**42**  
dB



**215 m<sup>3</sup>/h**



ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2016

1254/2014

357PP0303