

Sieniniai oro kondicionieriai AUX HALO DELUXE



Modeliai	AUX-09HE	AUX-12HE	AUX-18HE	AUX-24HE
Galia, kW (šald./šild.)	2,75 (0,50~3,20) kW 3,10 (0,50~3,40) kW	3,60 (0,80~3,70) kW 3,80 (1,00~3,90) kW	5,50 (1,20~5,70) kW 5,90 (1,20~6,10) kW	7,30 (1,40~7,60) kW 7,30 (0,90~7,50) kW
Elektros sąnaudos, kW (šald./šild.)	0,93 kW / 1,22 kW	1,13 kW / 1,24 kW	1,73 kW / 1,89 kW	2,30 kW / 2,50 kW
Įtampa, V/Hz	~220-240 / 1 / 50	~220-240 / 50	~220-240 / 50	~220-240 / 50
SEER / SCOP	6,16 / 4,17	6,12 / 4,14	6,57 / 4,02	6,89 / 4,11
Energijos efektyvumo klasė šaldant/šildant	A++ / A+	A++ / A+	A++ / A+	A++ / A+
Triukšmo lygis dB (A) Vidinis blokas min.-max. / išorinis blokas	19-22-27-31-38 / 40	20-23-29-32-38 / 42	23-26-31-32-41 / 44	23-31-33-36-38 / 45
Oro srautas (vid.blokas) (m3/val)	600	600	850	1150
Matmenys, mm (WxHxD) vid./išor.	788x292x198 / 730x545x285	788x292x198 / 730x545x285	940x316x224 / 800x545x315	1121x329x231 / 900x700x350
Vid./išor. bloko svoris neto, kg	8,0 / 25,0	8,5 / 25,0	12,0 / 35,0	14,0 / 45,0
Vamzdynas	1/4" - 3/8"	1/4" - 3/8"	1/4" - 1/2"	3/8" - 5/8"
Vamzdyno max ilgis/aukštis	20 / 10	20 / 10	20 / 10	25 / 15
Freono R32 kiekis, g (iki 5 m) / papildymas virš 5 m. g/m	530 / 20	600 / 20	1280 / 20	1440 / 30
El. maitinimas / laido storis	išorinis blokas 3x1,5mm ²	išorinis blokas 3x1,5mm ²	išorinis blokas 3x1,5mm ²	išorinis blokas 3x1,5mm ²
Valdymo laidas tarp bloku	5x1,5	5x1,5	5x1,5	5x1,5
Darbinės temperatūros ribos šaldymas/šildymas*	-10 - +50 / -20 - +24	-10 - +50 / -20 - +24	-10 - +50 / -20 - +24	-10 - +50 / -20 - +24

