

TECHNICAL PARAMETERS DATASHEET

Model(s):	CH-HP15UIMPZM
Air to water heat pump:	YES
Water to water heat pump:	NO
Brine to water heat pump:	NO
Low temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	AVERAGE
Parameters are declared for medium temperature application.	

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	9,319	kW	Seasonal space heating energy efficiency	η_{sh}	155,1	%
Declared capacity for heating for part load at indoor temperature 20 C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 C and outdoor temperature Tj			
Tj = -7 °C	Pah	8,244	kW	Tj = -7 °C	COPa	3,21	88
Tj = 2 °C	Pah	5,062	kW	Tj = 2 °C	COPa	4,99	54
Tj = 7 °C	Pah	5,814	kW	Tj = 7 °C	COPa	6,74	35
Tj = 12 °C	Pah	6,599	kW	Tj = 12 °C	COPa	8,74	15
Tj = bivalent temperature	Pah	8,244	kW	Tj = bivalent temperature	COPa	3,21	88
Tj = operating limit	Pah	9,396	kW	Tj = operating limit	COPa	2,88	100
For air-to-water heat pumps: Tj = -15C	Pah	-	kW	For air-to-water heat pumps: Tj = -15C	COPa	-	-
Bivalent temperature	Tbiv	-7	°C	For air to water heat pumps: Operation limit temperature	ToL	-10	°C
Cycling interval capacity for heating	Pcyc	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient(**)	Cdh	0,99	-	Heating water operating limit T	WROL	-	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	Poff	0,008	kW	Rated heat output (**)	Psup	-	kW
Standby mode	Psb	0,008	kW	Type of energy input		-	
Thermostat - off mode	Pto	0,008	kW				
Crankcase heater mode	Pck	0,064	kW				

Other items							
Capacity control	variable			For air to water heat pumps: Rated air flow rate, outdoors	-	-	m ³ /h
Sound power level, indoors/outdoors	LWA	56	dB	For water or brine to water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h
Annual energy consumption	QHE	4844	kWh				

For heat pump combination heater							
Declared load profile				Water heating energy efficiency			%
Daily electricity consumption	Qdec	-	kWh	Daily fuel consumption	Qfuel		kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC		GJ

Contact details	Cooper and Hunter International Corporation Road, Dagang town, Nansha, Guangzhou, P.R. China	No.3, Tianyuan
-----------------	---	----------------

(*) For heat pump space heaters and head pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and rated heat output of supplementary heater Psup is equal to the supplementary caoacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.