

Išoriniai blokai

Modeliai	M2OD-18HFN8-QA	M3OF-27HFN8-QA	M4OE-28HFN8-Q	M4OB-36HFN8-Q	M5OD-42HFN8-Q
Galingumas, kW (šald./šild.)	5.3 / 5.6	7.9 / 7.9	8.2 / 8.8	10.6 / 11.1	12.3 / 12.3
Vidinių blokų kiekis	1~2	1~3	1~4	1~4	1~5
Vidutinis el. gal., kW (šald./šild.)	1.63 / 1.50	2.45 / 2.12	2.25 / 2.37	3.52 / 3.17	3.80 / 3.32
Maksimalus el.gal., kW	2,85	3,6	4,15	4,6	4,7
SEER / SCOP	6,10 / 4,00 A++ / A+	6,10 / 4,00 A++ / A+	6,80 / 4,00 A++ / A+	6,50 / 4,00 A++ / A+	6,50 / 4,00 A++ / A+
Triukšmo lygis dB (A) maks.	56	53	62	63	62
Oro srautas (m3/val)	2202	2700	3798	4002	3852
Matmenys, mm (WxDxH)	800x333x554	845x363x702	946x410x810	946x410x810	946x410x810
Svoris, kg neto/bruto	35.5 / 38.5	51.1 / 55.8	62.1 / 67.7	68.8 / 75.6	73.3 / 80.4
Valdymo laidas tarp bloku	4x1.5	4x1.5	4x1.5	4x1.5	4x1.5
El. maitinimas	3x2.5	3x2.5	3x4.0	3x4.0	3x4.0
Bendras maksimalus atstumas, m	40	60	80	80	80
Maksimalus atstumas iki 1 vidinio, m	25	30	35	35	35
Maksimalus aukščių skirtumas vidinis/išorinis, m	15	15	15	15	15
Maksimalus aukščių skirtumas vidinis/vidinis, m	10	10	10	10	10
Freono R32 kiekis, kg	1,3	1,57	2,1	2,1	2,1
Freono pajungimai	1/4-3/8 x2	1/4-3/8 x3	1/4-3/8 x3 1/4-1/2 x1	1/4-3/8 x3 1/4-1/2 x1	1/4-3/8 x4 1/4-1/2 x1
Darbinės temperatūros ribos šald. / šild.	-15 ~ +50 / -15 ~ +24	-15 ~ +50 / -15 ~ +25	-15 ~ +50 / -15 ~ +25	-15 ~ +50 / -15 ~ +25	-15 ~ +50 / -15 ~ +25
Kaina EUR be PVM	1 076 €	1 350 €	1 554 €	1 771 €	1 993 €
Kaina EUR su PVM	1 302 €	1 634 €	1 880 €	2 143 €	2 412 €



Available combinations of indoor units

Cooling capacity 5.3 kW

M2OD-18HFN8-QA	
1 UNIT	2 UNITS
9	9+9
12	9+12
18	9+18
	12+12

Cooling capacity 7.9 kW

M3OF-27HFN8-QA		
1 UNIT	2 UNITS	3 UNITS
9	9+9	9+9+9
12	9+12	9+9+12
18	9+18	9+12+12
	12+12	
	12+18	

Cooling capacity 8.2 kW

M4OE-28HFN8-Q			
1 UNIT	2 UNITS	3 UNITS	4 UNITS
9	9+9	9+9+9	9+9+9+9
12	9+12	9+9+12	9+9+9+12
18	9+18	9+9+18	
	12+12	12+12+18	
	12+18	12+12+12	
	18+18		

Cooling capacity 10.6 kW

M4OB-36HFN8-Q					
1 UNIT	2 UNITS	3 UNITS		4 UNITS	
9	9+9	9+9+9	12+12+12	9+9+9+9	9+12+12+18
12	9+12	9+9+12	12+12+18	9+9+9+12	12+12+12+12
18	9+18	9+9+18	12+18+18	9+9+9+18	
	12+12	9+12+12	12+12+12	9+9+12+12	
	12+18	9+12+18	12+12+18	9+9+12+18	
	18+18	9+18+18	12+18+18	9+12+12+12	

Cooling capacity 12.3 kW

M5OD-42HFN8-Q										
1 UNIT	2 UNITS		3 UNITS			4 UNITS			5 UNITS	
9	9+9	12+18	9+9+9	9+12+18	12+12+24	9+9+9+9	9+9+12+18	9+12+12+24	9+9+9+9+9	9+9+12+12+12
12	9+12	12+24	9+9+12	9+12+24	12+18+18	9+9+9+12	9+9+12+24	9+12+18+18	9+9+9+9+12	9+12+12+12+12
18	9+18	18+18	9+9+18	9+18+18	18+18+18	9+9+9+18	9+9+18+18	12+12+12+12	9+9+9+9+18	
24	9+24	18+24	9+9+24	12+12+12		9+9+9+24	9+12+12+12	12+12+12+18	9+9+9+12+12	
	12+12		9+12+12	12+12+18		9+9+12+12	9+12+12+18		9+9+9+12+18	